

# Thin Client to Proxmox

Use this:

[https://www.apalrd.net/posts/2022/raspi\\_spice/](https://www.apalrd.net/posts/2022/raspi_spice/)

script:

```
#!/bin/bash
set -e

# Set auth options
PASSWORD='remote1234'
USERNAME='remote@pve'

# Set VM ID
VMID="601"

# Set Node
# This must either be a DNS address or name of the node in the cluster
NODE="liz"

# Proxy equals node if node is a DNS address
# Otherwise, you need to set the IP address of the node here
PROXY="10.11.12.10"

#The rest of the script from Proxmox
NODE="${NODE%.*}"

DATA="$(curl -f -s -S -k --data-urlencode "username=$USERNAME" --data-urlencode
"password=$PASSWORD" "https://$PROXY:8006/api2/json/access/ticket")"

echo "AUTH OK"

TICKET="${DATA//\"/}"
TICKET="${TICKET##*ticket:}"
TICKET="${TICKET%*,*}"
TICKET="${TICKET%\}*}"
```

```
CSRF="${DATA//\\"/>

```

## Touchpad configs:

Add `/etc/X11/xorg.conf.d/40-libinput.conf`

```
Section "InputClass"
    Identifier "libinput touchpad catchall"
    MatchIsTouchpad "on"
    MatchDevicePath "/dev/input/event*"
    Driver "libinput"
    Option "Tapping" "on"
    Option "NaturalScrolling" "true"
EndSection
```

Revision #6

Created 27 October 2023 20:24:36 by joscha.mijailovic

Updated 5 November 2024 00:57:34 by joscha.mijailovic