

Thin Client to Proxmox

Use this:

https://www.apalrd.net/posts/2022/raspi_spice/

script:

```
#!/bin/bash
set -e

# Set auth options
PASSWORD='remote1234'
USERNAME='remote@pve'

# Set VM ID
VMID="601"

# Set Node
# This must either be a DNS address or name of the node in the cluster
NODE="liz"

# Proxy equals node if node is a DNS address
# Otherwise, you need to set the IP address of the node here
PROXY="10.11.12.10"

#The rest of the script from Proxmox
NODE="{NODE%%\.*}"

DATA="$(curl -f -s -S -k --data-urlencode "username=$USERNAME" --data-urlencode
"password=$PASSWORD" "https://$PROXY:8006/api2/json/access/ticket")"

echo "AUTH OK"

TICKET="{DATA//\\"/}"
TICKET="{TICKET##*ticket:}"
TICKET="{TICKET%%,*}"
```

```
TICKET="${TICKET%%\}*}"
```

```
CSRF="${DATA//\ "/"}"
```

```
CSRF="${CSRF##*CSRFPreventionToken:}"
```

```
CSRF="${CSRF%%,*}"
```

```
CSRF="${CSRF%%\}*}"
```

```
curl -f -s -S -k -b "PVEAuthCookie=$TICKET" -H "CSRFPreventionToken: $CSRF"  
"https://$PROXY:8006/api2/spiceconfig/nodes/$NODE/qemu/$VMID/spiceproxy" -d "proxy=$PROXY" >  
spiceproxy
```

```
#Launch remote-viewer with spiceproxy file, in kiosk mode, quit on disconnect
```

```
#The run loop will get a new ticket and launch us again if we disconnect
```

```
exec remote-viewer -k --kiosk-quit on-disconnect spiceproxy
```

Touchpad configs:

Add `/etc/X11/xorg.conf.d/40-libinput.conf`

```
Section "InputClass"  
    Identifier "libinput touchpad catchall"  
    MatchIsTouchpad "on"  
    MatchDevicePath "/dev/input/event*"  
    Driver "libinput"  
    Option "Tapping" "on"  
    Option "NaturalScrolling" "true"  
EndSection
```

Revision #6

Created 2023-10-27 20:24:36 UTC by joscha.mijailovic

Updated 2024-11-05 00:57:34 UTC by joscha.mijailovic